



P16HP, P16HPZ, P16AP, P16APZ

FAST AND RELIABLE FOR FIELD SERVICE REPAIRS

Finn-Power P16 series crimping machines are compact, strong and reliable for any service crimping need. Their compact design allows efficient working and easy transport between any locations. P16 machines are easy to use and they produce high quality crimping day after day.

CONTROL

M MANUAL CONTROL

AVAILABLE MODELS

Z SEPARATED CRIMPING HEAD AND BODY

HP HAND PUMP FOR EASY FIELD SERVICE

AP AIR PRESSURE FOR EASY FIELD SERVICE

DIE SET P16

| Pno | Crimp. range | D | L |
|----------|--------------|----|----|
| 18212/10 | 10.0 - 12.0 | 10 | 55 |
| 18212/12 | 12.0 - 14.0 | 12 | 55 |
| 18212/14 | 14.0 - 16.0 | 14 | 55 |
| 18212/16 | 16.0 - 19.0 | 16 | 55 |
| 18212/19 | 19.0 - 23.0 | 19 | 55 |
| 18212/23 | 23.0 - 27.0 | 23 | 55 |
| 18212/27 | 27.0 - 31.0 | 27 | 65 |
| 18212/31 | 31.0 - 38.0 | 31 | 65 |

FEATURES

DIE SETS

CRIMPING RANGE (MM) ⁽¹⁾

CRIMPING RANGE (INCH) ⁽¹⁾

MAX OPENING (MM)

MAX CRIMPING FORCE (KN)

MAX CRIMPING FORCE (TON.)

NUMBER OF CRIMPS/HOUR ⁽²⁾

PUMP

PUMP

WEIGHT (KG)

WEIGHT (LBS)

MEASUREMENTS

- With standard dies. Crimping range can be increased with special dies.
- Theoretical with 10 mm cycle.



P16HP - PORTABLE



P16HPZ - FLEXIBLE



P16AP - COMPACT



P16APZ - FLEXIBLE


Manually operated hydraulic crimping machine for repair workshops. Easy to use, lightweight and compact in size.

Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.

Suitable for workshops where compressed air is available. This lightweight machine can easily be carried by hand in need of relocation.


Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.

331 mm / 13.1"




271 mm / 10.7"

331 mm / 13.1"




324 mm / 12.7"

331 mm / 13.1"



271 mm / 10.7"

241 mm / 9.5"



324 mm / 12.7"